

LONGREACH PRESS

Roof	<input type="checkbox"/>
Wall	<input type="checkbox"/>
Floor	<input checked="" type="checkbox"/>
Sawing	<input type="checkbox"/>
Timber Joining	<input type="checkbox"/>
Production Tools	<input type="checkbox"/>



- Simple to operate
- Simple to maintain
- Dual-sided controls
- Air driven clamping
- Robust construction

LONGREACH

The Longreach Press longitudinal drive is by an electric gear brake motor that incorporates soft start components and has in-built control to stop the Press travel.

Operation of the Longreach 1500 Press is simple. After training, no other skills are required. The simple electric hand controls minimise fatigue and increases production.

The machine and table are self-supporting and portable. This feature eliminates costly installation preparations although careful levelling is necessary. Once a location is established, the machine table should be shimmed and bolted to the floor.

SPECIFICATIONS

		Dimensions	
Overall dimensions (std unit)	- length (table)	12	m
	- width	2.2	m
Table width		1500	mm
Travel speed		0.7m/sec	m/min
Weight (approx.)		11200	kg

Installation requirements

Power	415V, 3-phase, 5-wire, 15A
Air	< 40 psi (max pressure)
Foundation	100mm (min.) level, sound concrete floor

RELATED EQUIPMENT

- Overhead materials handling system
- Finished goods trolleys
- Pryda Production Viewer software